



NovaSpray HFC 245fa

PERFOMANCES

The **NovaSpray™ HFC 245fa** is an aerosol grade pentafluoropropane. With a constant quality, it meets all the requirements of the aerosol industry.

Its **non-flammability** allows a wide range of formulations requiring safety measures (*regulations, hazardous environments, confined spaces*).

Because of its low **boiling point** it shows **endothermic properties** useful for cooling strained muscles. It is therefore frequently used in this type of formulation.

More economical than other non flammable solvents, it has no effect on the ozone layer and a negligible impact on the greenhouse effect.

SPECIFICATIONS

Standard Characteristics	Limit values
Appearance	Clear
Purity	≥ 99.8 % weight
Moisture content	≤ 100 ppm weight
Chloride ion test	negative

CHARACTERISTICS

		Units	Values
Chemical formula			CF ₃ -CH ₂ -CHF ₂
Chemical name			1,1,1,3,3-pentafluoropropane
Molecular weight		g/mol	134
Boiling point	at 1.013 bar	°C	15.3
Liquid density	at 20°C at 50°C	kg/dm ³	1.32 1.27
Relative pressure	saturating vapor at 20°C saturating vapor at 50°C	bar	1.2 3.5
Kauri-Butanol index			6
HFC 245fa solubility	in water at 25°C	% weight	0.72
Water solubility	in HFC 245fa at 25°C	% weight	0.16
Lower flammability limit	in the air at 20°C	% volume	none
Upper flammability limit	below 1.013 bar	% volume	none
Auto-ignition temperature		°C	412



PACKAGING

	Bottles	Container	Bulk
Capacity (liter)	27	88	5 to 20 T
Tare (kg)	16	38	
Load (kg)	30	70	
Diameter (mm)	300	300	
Height (mm)	630	1530	
Outflow external diameter (mm)	21.7	21.7	
Tap: right pitch (mm)	1.814	1.814	
Test pressure (bar)	33	33	

- Packaging technical characteristics are available upon request to the commercial department.
- Feasibility of filling packaging of the customers if they are in conformity with the legislation.
- Contact us for any other specific packaging.

STORAGE AND SHELF LIFE

Precautions for handling and storage :

French plants are controlled by the regulation of listed Establishments and have to comply with it (or with the local legislation).

- All packaging will be stored in a dry, well ventilated, easily accessible place, sheltered from sunlight and bad weather, away from any ignition source.
- It is recommended to store all packaging either in a specific place or isolated and sheltered by a fence.
- All packaging and piping will be grounded to discharge static electricity.
- Leak detectors, put at ground level, will be connected to an audible alarm, which will trigger in the event of leaks.
- The whole equipment will be tested with an appropriate leak detector before use.
- Material and electrical equipment in an explosive atmosphere will comply with the regulations (*grounding, equipotential bonding, ATEX material*).

Climalife can study the set up and assembling of your storage tanks, piping, and pumps, according to the prevailing regulations

Shelf life: unlimited (if appropriate storage conditions)



CONDITIONS OF USE

Please refer to the Material Safety Data Sheet (MSDS) before using the product.
Workers handling the product should be trained about risks and preventive measures.

The product is compatible with:

COMPATIBILITY	INCOMPATIBILITY
<p>Plastics:</p> <ul style="list-style-type: none">▪ Polyurethane▪ Polyvinyl chloride (PVC)▪ Polypropylene▪ Polyethylene▪ Teflon <p>Elastomers:</p> <ul style="list-style-type: none">▪ BUNA N®▪ Natural rubbers <p>Metals:</p> <ul style="list-style-type: none">▪ Ordinary steel▪ Stainless steel	<ul style="list-style-type: none">▪ Strong bases▪ Oxidizing agents

The information above is intended as a guide only. We assume no liability for its accuracy on its use. The user should make its own tests under its conditions in order to determine the suitability of any compound in a peculiar application.

Handle :

- **away from heat sources (flames or hot metallic surfaces)**
- **in cool and aired premises**

HEALTH SAFETY ENVIRONMENT (HSE)

Consult the Material Safety Datasheet (MSDS) on the website: www.quickfds.com

This data is based on information that the manufacturer believed to be reliable and offered in good faith. In no event will Climalife be responsible for special, incidental and consequential damages. The user is responsible, to the Administrative Authorities (Regulation of the listed establishments for the protection of the environment), for the conformity of his installation.