

SUNISOTM SL

WORLD-LEADING REFRIGERATION FLUIDS



Introduction

SUNISO® SL lubricants are high-performance, fully synthetic refrigeration fluids formulated for optimal performance of compressors using HFC refrigerants. Manufactured with specially engineered polyol esters (POE), Suniso SL fluids ensure superior miscibility and efficient oil return throughout the system, from the evaporator to the compressor. In addition, Suniso SL fluids retain viscosity very well with the refrigerant dissolved, offering maximum protection to compressor bearings. Suniso SL fluids deliver exceptional thermal stability, making them suitable for applications ranging from low temperature refrigeration systems to high temperature heat pumps.

Applications

SUNISO SL lubricants are recommended for use in refrigeration, air-conditioning and heat pump systems utilizing ozone friendly, chlorine-free refrigerants. Compatible with all HFC refrigerants (e.g. R-125, R-134a, R-143a, R-152a, R-404A, R-407C, R-410A and R-507A) Suniso SL fluids exhibit exceptional miscibility even at extremely low temperatures. They are suitable for a wide range of compressor types, including reciprocating, screw, centrifugal, and scroll compressors found in applications such as petrochemical, cold storage, trucking, supermarkets and home air-conditioning systems.

FEATURES & BENEFITS



MISCIBILITY WITH HFC REFRIGERANTS

Promotes efficient oil return from evaporator to compressor, thereby preventing oil buildup in the evaporator and other system components, minimizing the risk of reduced system efficiency and damage.



OPTIMAL VISCOSITY RETENTION

Balanced formulation avoids excessive viscosity reduction due to the dilution of the lubricant by the refrigerant. This helps maintain a protective lubricating film across a wide temperature range, reducing friction and preventing metal-to-metal contact.



HIGH THERMAL STABILITY

Suitable for a wide range of applications ranging from low temperature refrigeration systems to high temperature heat pumps.



SPECIFICATIONS

DIN 51503 KD
ISO 6743-3 ISO-L-DRD

Typical Performance Data

Property	ASTM Method	SL 22	SL 32	SL 46	SL 68	SL 100	SL 170	SL 220
Density @ 15°C, kg/L	D4052	0.993	0.993	0.981	0.973	0.966	0.969	0.966
Viscosity @ 40°C, cSt	D445	23.5	32.0	46.1	65.0	100.0	167.8	217.0
Viscosity @ 100°C, cSt	D445	4.4	5.6	6.9	8.3	10.9	15.3	17.9
Moisture, ppm	D6304	<100	<100	<100	<100	<100	<100	<100
Flash Point, °C / °F	D92	252 / 486	250 / 482	253 / 487	255 / 491	270 / 518	279 / 534	255 / 491
Pour Point, °C / °F	D5950	-57 / -71	-54 / -65	-48 / -54	-36 / -33	-33 / -27	-27 / -17	-30 / -22
Acid Value, mg KOH/gm	D974 (Modified)	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1

The values quoted above are typical of normal production. They do not constitute a specification.



Committed to the disciplined operation of our business.

CERTIFIED

ISO 9001: 2015

ISO 14001: 2015

IAFT 16949: 2016



SUNISO™

Learn more about us: sunisolubricants.com

Petro-Canada Lubricants Inc.

2310 Lakeshore Road West, Mississauga, ON, Canada L5J 1K2

petrocanadalubricants.com

Petro-Canada Lubricants is an HF Sinclair Brand.

Trademarks are owned or used under license.

IM-8232UK (2024.07)